



FA370

Led Beacon, intrinsic safe, red lens

General

The FA370 is a LED beacon for use in intrinsic safe areas, to provide a visual warning signal in case of fire. It carries EEx ia IIC T4 rating, and has a ABS flame retardant housing with IP65 rating.

Intrinsically Safe Area

The FA370 is ATEX approved with ExII 1G and EEx ia IIC T4 ratings. It is housed in flame retardant ABS with UL94V0 & 5VA rating, and offers IP65 ingress protection.

Efficient and versatile

The FA370 beacon utilises 6 high intensity LED's and a prismatic lens for effective visual warning and greater spread of light.



Standard Features

- ATEX approved
- EEx ia IIC T4 rating
- IP65
- High efficiency LED's

FA370

Led Beacon, intrinsic safe, red lens

Specifications

Operation	Continuous
Supply voltage	6 - 28 VDC
Current consumption	48mA
Flash rate	60 or 120 /min.
Line monitoring input	Polarised input
Housing	ABS flame retardant
Ingress protection	IP65
Operating temperature	-40°C to +60°C
Dimensions (Ø x D)	89 x 85 mm
Weight	350g
Color housing	Red
Color lens	Red

Ordering Information

Part No.	Description
FA370	Led Beacon, intrinsic safe, red lens
AS372	Fire sounder, intrinsic safe, multi tone, surface mount
AS374	Fire sounder, hazardous area, multi tone, horn
FA370C	Led Beacon, intrinsic safe, clear lens
FA375	5J Xenon Beacon, hazardous area, red lens
FA375Y	5J Xenon Beacon, hazardous area, yellow/amber lens
GBX370	I.S. Galvanic isolator for AS372/FA370 series



www.gesecurity.net

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit [GE Security online](http://www.gesecurity.net) or contact your GE Security sales representative.

IPS-FA370-2008-03-25 11:27:57 Released : 06.03.2008;