



FF766

Triple IR flame detector in Eexd - IIC T6 flame proof housing

General

The FF766 is a IR³ flame detector in a flame proof housing. IR³ models have excellent response to flame while providing superb immunity to extraneous sources. New micro-processor technology makes the detectors independent of flame intensity enabling it to operate through smoke, a layer of oil, dust, or water vapor. A high and low sensitivity setting according to EN54-10 is provided.

Installer and maintenance friendly

The units can be wired as conventional 2 wire, 4-20 mA, or relay contacts (fire, fault and pre alarm) in latching or non-latching operation. Remote test inputs are available to activate self-test.

A stainless steel adjustable bracket and weather shield is also available.

The units are tolerant to vibration, and wind does not affect the performance. The IR³ unit has excellent tolerance to detector window contamination and can detect flame through glass windows.

A flame sensor test unit is available for accurate testing of the detectors.

Reducing false alarms

Most IR flame sensors respond to 4.3 m light, emitted by hydrocarbon flames. By responding to 0.75 to 2.7 m light emitted by every fire, all flickering flames can be detected. Gas fires not visible to the naked eye e.g. hydrogen may also be detected.

The IR³ detectors, responding to adjacent IR wavelengths, enable it to discriminate between flames and spurious sources of IR radiation.

The combination of filters and signal processing allows the sensor to be used without risk of false alarms in difficult situations characterised by factors such as flickering sunlight.



Standard Features

- Triple IR detector
- High specification units for critical applications
- IP66 Housing
- Flame proof housing
- Low current consumption
- 2 Wire, 4 - 20 mA and relay operation
- Latching and non latching operation
- High / Low sensitivity setting
- Tolerance to detector window contamination
- Remote self test facility
- Microprocessor controlled
- Immunity to false sources (arc welding, lightning and static)
- EN54-10 & CPD approved

FF766

Triple IR flame detector in Eexd - IIC T6 flame proof housing

Specifications

| | |
|------------------------|-------------------------------|
| Supply voltage | 14 - 30 VDC |
| Supply current | 3/9, 4/8/14, 4-20, 8-20 mA |
| Relay contact ratings | 1 A @ 30 VDC (resistive load) |
| Field of view | 90° min. cone |
| Spectral response (IR) | 0.75 to 2.7 microm |
| Operating temperature | -10°C to 55°C |
| Storage temperature | -20°C to 65°C |
| Relative humidity | 95% non-condensing |
| IP Rating | IP66 |
| Weight | 2.5 kg |
| Dimensions | |
| W x H x D | 146 x 150 x 137 mm |
| IEC marking | EEx d IIC T6 |

Ordering Information

| Part No. | Description |
|----------|--|
| FF766 | Triple IR flame detector in Eexd - IIC T6 flame proof housing |
| FF762 | Triple IR flame detector in die-cast zinc alloy housing |
| FF767 | Triple IR Intrinsic safe flame detector in die-cast zinc alloy housing |
| FF703 | UV/IR universal test torch |
| FF704 | Portable Bunsen burner for flame detector testing |
| FF705 | Adjustable mounting bracket |



www.gesecurity.net

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-FF766-2008-12-2 12:42:48 Released : 31.07.2008;